

## NAG Library Function Document

### nag\_opt\_sparse\_nlp\_option\_get\_integer (e04vrc)

#### 1 Purpose

nag\_opt\_sparse\_nlp\_option\_get\_integer (e04vrc) is used to get the value of an Integer optional parameter. nag\_opt\_sparse\_nlp\_option\_get\_integer (e04vrc) can be used before or after calling nag\_opt\_sparse\_nlp\_solve (e04vhc).

#### 2 Specification

```
#include <nag.h>
#include <nage04.h>

void nag_opt_sparse_nlp_option_get_integer (const char *string,
      Integer *ivalue, Nag_E04State *state, NagError *fail)
```

#### 3 Description

nag\_opt\_sparse\_nlp\_option\_get\_integer (e04vrc) obtains the current value of an integer option. For example

```
e04vrc ("Major Iterations", &itnlim, &state, &fail);
```

will result in the value of the optional parameter **Major Iterations Limit** being output in itnlim.

A complete list of optional parameters, their abbreviations, synonyms and default values is given in Section 12 in nag\_opt\_sparse\_nlp\_solve (e04vhc).

#### 4 References

None.

#### 5 Arguments

- 1: **string** – const char \* *Input*  
*On entry:* a single valid keyword of an Integer optional parameter (as described in Section 12 in nag\_opt\_sparse\_nlp\_solve (e04vhc)).
- 2: **ivalue** – Integer \* *Output*  
*On exit:* the Integer value associated with the keyword in **string**.
- 3: **state** – Nag\_E04State \* *Communication Structure*  
**state** contains internal information required for functions in this suite. It must not be modified in any way.
- 4: **fail** – NagError \* *Input/Output*  
The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

### NE\_BAD\_PARAM

On entry, argument *<value>* had an illegal value.

### NE\_E04\_OPTION\_INVALID

The supplied option string is invalid. Check that the keywords are neither ambiguous nor misspelt. The option string is '*<value>*'.

### NE\_E04VGC\_NOT\_INIT

The initialization function `nag_opt_sparse_nlp_init` (e04vgc) has not been called.

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

### NE\_NO\_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

## 7 Accuracy

Not applicable.

## 8 Parallelism and Performance

`nag_opt_sparse_nlp_option_get_integer` (e04vrc) is not threaded in any implementation.

## 9 Further Comments

None.

## 10 Example

See Section 10 in `nag_opt_sparse_nlp_option_set_file` (e04vkc).

---