

NAG Library Function Document

nag_real_tridiag_lin_solve (f04bcc)

1 Purpose

`nag_real_tridiag_lin_solve (f04bcc)` computes the solution to a real system of linear equations $AX = B$, where A is an n by n tridiagonal matrix and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

```
#include <nag.h>
#include <nagf04.h>

void nag_real_tridiag_lin_solve (Nag_OrderType order, Integer n,
                                Integer nrhs, double dl[], double d[], double du[], double du2[],
                                Integer ipiv[], double b[], Integer pdb, double *rcond, double *errbnd,
                                NagError *fail)
```

3 Description

The LU decomposition with partial pivoting and row interchanges is used to factor A as $A = PLU$, where P is a permutation matrix, L is unit lower triangular with at most one nonzero subdiagonal element, and U is an upper triangular band matrix with two superdiagonals. The factored form of A is then used to solve the system of equations $AX = B$.

Note that the equations $A^T X = B$ may be solved by interchanging the order of the arguments **du** and **dl**.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia <http://www.netlib.org/lapack/lug>

Higham N J (2002) *Accuracy and Stability of Numerical Algorithms* (2nd Edition) SIAM, Philadelphia

5 Arguments

1: **order** – Nag_OrderType *Input*

On entry: the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.3.1.3 in How to Use the NAG Library and its Documentation for a more detailed explanation of the use of this argument.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2: **n** – Integer *Input*

On entry: the number of linear equations n , i.e., the order of the matrix A .

Constraint: **n** ≥ 0 .

3: **nrhs** – Integer *Input*

On entry: the number of right-hand sides r , i.e., the number of columns of the matrix B .

Constraint: **nrhs** ≥ 0 .

4: **dl**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **dl** must be at least $\max(1, \mathbf{n} - 1)$.

On entry: must contain the $(n - 1)$ subdiagonal elements of the matrix *A*.

On exit: if **fail.code** = NE_NOERROR, **dl** is overwritten by the $(n - 1)$ multipliers that define the matrix *L* from the *LU* factorization of *A*.

5: **d**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **d** must be at least $\max(1, \mathbf{n})$.

On entry: must contain the *n* diagonal elements of the matrix *A*.

On exit: if **fail.code** = NE_NOERROR, **d** is overwritten by the *n* diagonal elements of the upper triangular matrix *U* from the *LU* factorization of *A*.

6: **du**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **du** must be at least $\max(1, \mathbf{n} - 1)$.

On entry: must contain the $(n - 1)$ superdiagonal elements of the matrix *A*

On exit: if **fail.code** = NE_NOERROR, **du** is overwritten by the $(n - 1)$ elements of the first superdiagonal of *U*.

7: **du2[n - 2]** – double *Output*

On exit: if **fail.code** = NE_NOERROR, **du2** returns the $(n - 2)$ elements of the second superdiagonal of *U*.

8: **ipiv[n]** – Integer *Output*

On exit: if **fail.code** = NE_NOERROR, the pivot indices that define the permutation matrix *P*; at the *i*th step row *i* of the matrix was interchanged with row **ipiv**[*i* − 1]. **ipiv**[*i* − 1] will always be either *i* or $(i + 1)$; **ipiv**[*i* − 1] = *i* indicates a row interchange was not required.

9: **b**[*dim*] – double *Input/Output*

Note: the dimension, *dim*, of the array **b** must be at least

$\max(1, \mathbf{pdb} \times \mathbf{nrhs})$ when **order** = Nag_ColMajor;
 $\max(1, \mathbf{n} \times \mathbf{pdb})$ when **order** = Nag_RowMajor.

The (i, j) th element of the matrix *B* is stored in

b[(*j* − 1) × **pdb** + *i* − 1] when **order** = Nag_ColMajor;
b[(*i* − 1) × **pdb** + *j* − 1] when **order** = Nag_RowMajor.

On entry: the *n* by *r* matrix of right-hand sides *B*.

On exit: if **fail.code** = NE_NOERROR or NE_RCOND, the *n* by *r* solution matrix *X*.

10: **pdb** – Integer *Input*

On entry: the stride separating row or column elements (depending on the value of **order**) in the array **b**.

Constraints:

if **order** = Nag_ColMajor, **pdb** $\geq \max(1, \mathbf{n})$;
if **order** = Nag_RowMajor, **pdb** $\geq \max(1, \mathbf{nrhs})$.

11: **rcond** – double * *Output*

On exit: if no constraints are violated, an estimate of the reciprocal of the condition number of the matrix *A*, computed as $\mathbf{rcond} = 1 / (\|\mathbf{A}\|_1 \|\mathbf{A}^{-1}\|_1)$.

12: **errbnd** – double * Output

On exit: if **fail.code** = NE_NOERROR or NE_RCOND, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \leq \text{errbnd}$, where \hat{x} is a column of the computed solution returned in the array **b** and x is the corresponding column of the exact solution X . If **rcond** is less than *machine precision*, then **errbnd** is returned as unity.

13: **fail** – NagError * Input/Output

The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

The Integer allocatable memory required is **n**, and the double allocatable memory required is $2 \times \mathbf{n}$. In this case the factorization and the solution X have been computed, but **rcond** and **errbnd** have not been computed.

See Section 2.3.1.2 in How to Use the NAG Library and its Documentation for further information.

NE_BAD_PARAM

On entry, argument $\langle \text{value} \rangle$ had an illegal value.

NE_INT

On entry, **n** = $\langle \text{value} \rangle$.

Constraint: **n** ≥ 0 .

On entry, **nrhs** = $\langle \text{value} \rangle$.

Constraint: **nrhs** ≥ 0 .

On entry, **pdb** = $\langle \text{value} \rangle$.

Constraint: **pdb** > 0 .

NE_INT_2

On entry, **pdb** = $\langle \text{value} \rangle$ and **n** = $\langle \text{value} \rangle$.

Constraint: **pdb** $\geq \max(1, \mathbf{n})$.

On entry, **pdb** = $\langle \text{value} \rangle$ and **nrhs** = $\langle \text{value} \rangle$.

Constraint: **pdb** $\geq \max(1, \mathbf{nrhs})$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.

See Section 2.7.6 in How to Use the NAG Library and its Documentation for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.

See Section 2.7.5 in How to Use the NAG Library and its Documentation for further information.

NE_RCOND

A solution has been computed, but **rcond** is less than *machine precision* so that the matrix A is numerically singular.

NE_SINGULAR

Diagonal element $\langle value \rangle$ of the upper triangular factor is zero. The factorization has been completed, but the solution could not be computed.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A + E)\hat{x} = b,$$

where

$$\|E\|_1 = O(\epsilon)\|A\|_1$$

and ϵ is the **machine precision**. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \leq \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1\|A\|_1$, the condition number of A with respect to the solution of the linear equations. nag_real_tridiag_lin_solve (f04bcc) uses the approximation $\|E\|_1 = \epsilon\|A\|_1$ to estimate **errbnd**. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Parallelism and Performance

nag_real_tridiag_lin_solve (f04bcc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the x06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this function. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The total number of floating-point operations required to solve the equations $AX = B$ is proportional to nr . The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogue of nag_real_tridiag_lin_solve (f04bcc) is nag_complex_tridiag_lin_solve (f04ccc).

10 Example

This example solves the equations

$$AX = B,$$

where A is the tridiagonal matrix

$$A = \begin{pmatrix} 3.0 & 2.1 & 0 & 0 & 0 \\ 3.4 & 2.3 & -1.0 & 0 & 0 \\ 0 & 3.6 & -5.0 & 1.9 & 0 \\ 0 & 0 & 7.0 & -0.9 & 8.0 \\ 0 & 0 & 0 & -6.0 & 7.1 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 2.7 & 6.6 \\ -0.5 & 10.8 \\ 2.6 & -3.2 \\ 0.6 & -11.2 \\ 2.7 & 19.1 \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

10.1 Program Text

```
/* nag_real_tridiag_lin_solve (f04bcc) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf04.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    double errbnd, rcond;
    Integer exit_status, i, j, n, nrhs, pdb;

    /* Arrays */
    double *b = 0, *d = 0, *dl = 0, *du = 0, *du2 = 0;
    Integer *ipiv = 0;

    /* Nag Types */
    NagError fail;
    Nag_OrderType order;

#define NAG_COLUMN_MAJOR
#define B(I, J) b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define B(I, J) b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

    exit_status = 0;
    INIT_FAIL(fail);

    printf("nag_real_tridiag_lin_solve (f04bcc) Example Program Results\n\n");

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif

#ifdef _WIN32
    scanf_s("%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", &n, &nrhs);
#else
    scanf("%" NAG_IFMT "%" NAG_IFMT "%*[^\n] ", &n, &nrhs);
#endif
    if (n >= 0 && nrhs >= 0) {
        /* Allocate memory */
        if (!(b = NAG_ALLOC(n * nrhs, double)) ||
            !(d = NAG_ALLOC(n, double)) ||
            !(dl = NAG_ALLOC(n - 1, double)) ||
            !(du = NAG_ALLOC(n - 1, double)) ||
            !(du2 = NAG_ALLOC(n - 2, double)) || !(ipiv = NAG_ALLOC(n, Integer)))
        {
            printf("Allocation failure\n");
            exit_status = -1;
            goto END;
        }
#endif
        NAG_COLUMN_MAJOR
        pdb = n;
#else

```

```

        pdb = nrhs;
#endif
}
else {
    printf("%s\n", "n and/or nrhs too small");
    exit_status = 1;
    return exit_status;
}
/* Read A and B from data file */
for (i = 1; i <= n - 1; ++i) {
#ifdef _WIN32
    scanf_s("%lf", &du[i - 1]);
#else
    scanf("%lf", &du[i - 1]);
#endif
}
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif
for (i = 1; i <= n; ++i) {
#ifdef _WIN32
    scanf_s("%lf", &d[i - 1]);
#else
    scanf("%lf", &d[i - 1]);
#endif
}
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif
for (i = 1; i <= n - 1; ++i) {
#ifdef _WIN32
    scanf_s("%lf", &dl[i - 1]);
#else
    scanf("%lf", &dl[i - 1]);
#endif
}
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif
for (i = 1; i <= n; ++i) {
    for (j = 1; j <= nrhs; ++j) {
#ifdef _WIN32
        scanf_s("%lf", &B(i, j));
#else
        scanf("%lf", &B(i, j));
#endif
    }
}
#ifdef _WIN32
    scanf_s("%*[^\n] ");
#else
    scanf("%*[^\n] ");
#endif
/* Solve the equations AX = B for X */
/* nag_real_tridiag_lin_solve (f04bcc).
 * Computes the solution and error-bound to a real
 * tridiagonal system of linear equations
 */
nag_real_tridiag_lin_solve(order, n, nrhs, dl, d, du, du2, ipiv, b, pdb,
                           &rcond, &errbnd, &fail);
if (fail.code == NE_NOERROR) {

```

```

/* Print solution, estimate of condition number and approximate */
/* error bound */
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                      nrhs, b, pdb, "Solution", 0, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}
printf("\n");
printf("%s\n      %10.1e\n", "Estimate of condition number", 1.0 / rcond);
printf("\n\n");

printf("%s\n      %10.1e\n\n",
       "Estimate of error bound for computed solutions", errbnd);
}
else if (fail.code == NE_RCOND) {
    /* Matrix A is numerically singular. Print estimate of */
    /* reciprocal of condition number and solution */

    printf("\n%s\n%6s%10.1e\n\n",
           "Estimate of reciprocal of condition number", "", rcond);
    /* nag_gen_real_mat_print (x04cac), see above. */
    fflush(stdout);
    nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n,
                          nrhs, b, pdb, "Solution", 0, &fail);
    if (fail.code != NE_NOERROR) {
        printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
               fail.message);
        exit_status = 1;
        goto END;
    }
}
else if (fail.code == NE_SINGULAR) {
    /* The upper triangular matrix U is exactly singular. Print */
    /* details of factorization */

    printf("%s\n\n", "Details of factorization");
    printf("%s\n", " Second superdiagonal of U");

    for (i = 1; i <= n - 2; ++i) {
        printf("%9.4f%s", du2[i - 1], i % 8 == 0 || i == n - 2 ? "\n" : " ");
    }
    printf("\n");

    printf("\n%s\n", " First superdiagonal of U");
    for (i = 1; i <= n - 1; ++i) {
        printf("%9.4f%s", du[i - 1], i % 8 == 0 || i == n - 1 ? "\n" : " ");
    }
    printf("\n\n");

    printf("%s\n", " Main diagonal of U");
    for (i = 1; i <= n; ++i) {
        printf("%9.4f%s", d[i - 1], i % 8 == 0 || i == n ? "\n" : " ");
    }
    printf("\n\n");

    printf("%s\n", " Multipliers");
    for (i = 1; i <= n - 1; ++i) {
        printf("%9.4f%s", dl[i - 1], i % 8 == 0 || i == n - 1 ? "\n" : " ");
    }
    printf("\n\n");

    printf("%s\n", " Vector of interchanges");
    for (i = 1; i <= n; ++i) {
        printf("%9" NAG_IFMT "%s", ipiv[i - 1], i % 8 == 0

```

```

        || i == n ? "\n" : " ");
    }
    printf("\n");
}
else {
    printf("Error from nag_real_tridiag_lin_solve (f04bcc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}
END:
NAG_FREE(b);
NAG_FREE(d);
NAG_FREE(d1);
NAG_FREE(du);
NAG_FREE(du2);
NAG_FREE(ipiv);

return exit_status;
}

```

10.2 Program Data

nag_real_tridiag_lin_solve (f04bcc) Example Program Data

```

5      2                      :Values of N and NRHS

      2.1  -1.0   1.9   8.0  :End of superdiagonal DU
3.0    2.3  -5.0  -0.9   7.1  :End of diagonal D
3.4    3.6   7.0  -6.0          :End of subdiagonal DL

      2.7   6.6
-0.5  10.8
2.6  -3.2
0.6 -11.2
2.7  19.1                  :End of matrix B

```

10.3 Program Results

nag_real_tridiag_lin_solve (f04bcc) Example Program Results

```

Solution
      1         2
1    -4.0000    5.0000
2     7.0000   -4.0000
3     3.0000   -3.0000
4    -4.0000   -2.0000
5    -3.0000    1.0000

```

```

Estimate of condition number
      9.3e+01

```

```

Estimate of error bound for computed solutions
      1.0e-14

```