

NAG Library Function Document

nag_mv_discrim (g03dac)

1 Purpose

nag_mv_discrim (g03dac) computes a test statistic for the equality of within-group covariance matrices and also computes matrices for use in discriminant analysis.

2 Specification

```
#include <nag.h>
#include <nagg03.h>
void nag_mv_discrim (Integer n, Integer m, const double x[], Integer tdx,
                     const Integer isx[], Integer nvar, const Integer ing[], Integer ng,
                     const double wt[], Integer nig[], double gmean[], Integer tdg,
                     double det[], double gc[], double *stat, double *df, double *sig,
                     NagError *fail)
```

3 Description

Let a sample of n observations on p variables come from n_g groups with n_j observations in the j th group and $\sum n_j = n$. If the data is assumed to follow a multivariate Normal distribution with the variance-covariance matrix of the j th group Σ_j , then to test for equality of the variance-covariance matrices between groups, that is, $\Sigma_1 = \Sigma_2 = \dots = \Sigma_{n_g} = \Sigma$, the following likelihood-ratio test statistic, G , can be used;

$$G = C \left\{ (n - n_g) \log |S| - \sum_{j=1}^{n_g} (n_j - 1) \log |S_j| \right\},$$

where

$$C = 1 - \frac{2p^2 + 3p - 1}{6(p+1)(n_g - 1)} \left(\sum_{j=1}^{n_g} \frac{1}{(n_j - 1)} - \frac{1}{(n - n_g)} \right),$$

and S_j are the within-group variance-covariance matrices and S is the pooled variance-covariance matrix given by

$$S = \frac{\sum_{j=1}^{n_g} (n_j - 1) S_j}{(n - n_g)}.$$

For large n , G is approximately distributed as a χ^2 variable with $\frac{1}{2}p(p+1)(n_g - 1)$ degrees of freedom, see Morrison (1967) for further comments. If weights are used, then S and S_j are the weighted pooled and within-group variance-covariance matrices and n is the effective number of observations, that is, the sum of the weights.

Instead of calculating the within-group variance-covariance matrices and then computing their determinants in order to calculate the test statistic, nag_mv_discrim (g03dac) uses a QR decomposition. The group means are subtracted from the data and then for each group, a QR decomposition is computed to give an upper triangular matrix R_j^* . This matrix can be scaled to give a matrix R_j such that $S_j = R_j^T R_j$. The pooled R matrix is then computed from the R_j matrices. The values of $|S|$ and the $|S_j|$ can then be calculated from the diagonal elements of R and the R_j .

This approach means that the Mahalanobis squared distances for a vector observation x can be computed as $z^T z$, where $R_j z = (x - \bar{x}_j)$, \bar{x}_j being the vector of means of the j th group. These distances

can be calculated by nag_mv_discrim_mahaldist (g03dbc). The distances are used in discriminant analysis and nag_mv_discrim_group (g03dcc) uses the results of nag_mv_discrim (g03dac) to perform several different types of discriminant analysis. The differences between the discriminant methods are, in part, due to whether or not the within-group variance-covariance matrices are equal.

4 References

- Aitchison J and Dunsmore I R (1975) *Statistical Prediction Analysis* Cambridge
 Kendall M G and Stuart A (1976) *The Advanced Theory of Statistics (Volume 3)* (3rd Edition) Griffin
 Krzanowski W J (1990) *Principles of Multivariate Analysis* Oxford University Press
 Morrison D F (1967) *Multivariate Statistical Methods* McGraw–Hill

5 Arguments

- 1: **n** – Integer *Input*
On entry: the number of observations, n .
Constraint: $\mathbf{n} \geq 1$.
- 2: **m** – Integer *Input*
On entry: the number of variables in the data array **x**.
Constraint: $\mathbf{m} \geq \mathbf{nvar}$.
- 3: **x[n × tdx]** – const double *Input*
On entry: $\mathbf{x}[(k - 1) \times \mathbf{tdx} + l - 1]$ must contain the k th observation for the l th variable, for $k = 1, 2, \dots, n$ and $l = 1, 2, \dots, \mathbf{m}$.
- 4: **tdx** – Integer *Input*
On entry: the stride separating matrix column elements in the array **x**.
Constraint: $\mathbf{tdx} \geq \mathbf{m}$.
- 5: **isx[m]** – const Integer *Input*
On entry: $\mathbf{isx}[l - 1]$ indicates whether or not the l th variable in **x** is to be included in the variance-covariance matrices.
 If $\mathbf{isx}[l - 1] > 0$ the l th variable is included, for $l = 1, 2, \dots, \mathbf{m}$; otherwise it is not referenced.
Constraint: $\mathbf{isx}[l - 1] > 0$ for **nvar** values of l .
- 6: **nvar** – Integer *Input*
On entry: the number of variables in the variance-covariance matrices, p .
Constraint: $\mathbf{nvar} \geq 1$.
- 7: **ing[n]** – const Integer *Input*
On entry: $\mathbf{ing}[k - 1]$ indicates to which group the k th observation belongs, for $k = 1, 2, \dots, n$.
Constraint: $1 \leq \mathbf{ing}[k - 1] \leq \mathbf{ng}$, for $k = 1, 2, \dots, n$
 The values of **ing** must be such that each group has at least **nvar** members

8:	ng – Integer	<i>Input</i>
	<i>On entry:</i> the number of groups, n_g .	
	<i>Constraint:</i> $\text{ng} \geq 2$.	
9:	wt[n] – const double	<i>Input</i>
	<i>On entry:</i> the elements of wt must contain the weights to be used in the analysis and the effective number of observations for a group is the sum of the weights of the observations in that group. If $\text{wt}[k - 1] = 0.0$ then the k th observation is excluded from the calculations.	
	If weights are not provided then wt must be set to NULL and the effective number of observations for a group is the number of observations in that group.	
	<i>Constraints:</i>	
	if wt is not NULL , $\text{wt}[k - 1] \geq 0.0$, for $k = 1, 2, \dots, n$;	
	the effective number of observations for each group must be greater than 1.	
10:	nig[ng] – Integer	<i>Output</i>
	<i>On exit:</i> nig [$j - 1$] contains the number of observations in the j th group, for $j = 1, 2, \dots, n_g$.	
11:	gmean[ng × tdg] – double	<i>Output</i>
	Note: the (i, j) th element of the matrix is stored in gmean [($i - 1$) \times tdg + $j - 1$].	
	<i>On exit:</i> the j th row of gmean contains the means of the p selected variables for the j th group, for $j = 1, 2, \dots, n_g$.	
12:	tdg – Integer	<i>Input</i>
	<i>On entry:</i> the stride separating matrix column elements in the array gmean .	
	<i>Constraint:</i> tdg $\geq \text{nvar}$.	
13:	det[ng] – double	<i>Output</i>
	<i>On exit:</i> the logarithm of the determinants of the within-group variance-covariance matrices.	
14:	gc[dim] – double	<i>Output</i>
	Note: the dimension, dim , of the array gc must be at least $(\text{ng} + 1) \times \text{nvar} \times (\text{nvar} + 1)/2$.	
	<i>On exit:</i> the first $p(p + 1)/2$ elements of gc contain R and the remaining n_g blocks of $p(p + 1)/2$ elements contain the R_j matrices. All are stored in packed form by columns.	
15:	stat – double *	<i>Output</i>
	<i>On exit:</i> the likelihood-ratio test static, G .	
16:	df – double *	<i>Output</i>
	<i>On exit:</i> the degrees of freedom for the distribution of G .	
17:	sig – double *	<i>Output</i>
	<i>On exit:</i> the significance level for G .	
18:	fail – NagError *	<i>Input/Output</i>
	The NAG error argument (see Section 2.7 in How to Use the NAG Library and its Documentation).	

6 Error Indicators and Warnings

NE_2_INT_ARG_LT

On entry, $\mathbf{m} = \langle value \rangle$ while $\mathbf{nvar} = \langle value \rangle$. These arguments must satisfy $\mathbf{m} \geq \mathbf{nvar}$.

On entry, $\mathbf{tdg} = \langle value \rangle$ while $\mathbf{nvar} = \langle value \rangle$. These arguments must satisfy $\mathbf{tdg} \geq \mathbf{nvar}$.

On entry, $\mathbf{tdx} = \langle value \rangle$ while $\mathbf{m} = \langle value \rangle$. These arguments must satisfy $\mathbf{tdx} \geq \mathbf{m}$.

NE_ALLOC_FAIL

Dynamic memory allocation failed.

NE_GROUP_OBSERV

On entry, group $\langle value \rangle$ has $\langle value \rangle$ effective observations.

Constraint: in each group the effective number of observations must be ≥ 1 .

NE_GROUP_VAR

On entry, group $\langle value \rangle$ has $\langle value \rangle$ members, while $\mathbf{nvar} = \langle value \rangle$.

Constraint: number of members in each group $\geq \mathbf{nvar}$.

NE_GROUP_VAR_RANK

The variables in group $\langle value \rangle$ are not of full rank.

NE_INT_ARG_LT

On entry, $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{n} \geq 1$.

On entry, $\mathbf{ng} = \langle value \rangle$.

Constraint: $\mathbf{ng} \geq 2$.

On entry, $\mathbf{nvar} = \langle value \rangle$.

Constraint: $\mathbf{nvar} \geq 1$.

NE_INTARR_INT

On entry, $\mathbf{ing}[\langle value \rangle] = \langle value \rangle$, $\mathbf{ng} = \langle value \rangle$.

Constraint: $1 \leq \mathbf{ing}[i - 1] \leq \mathbf{ng}$, for $i = 1, 2, \dots, n$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

NE_NEG_WEIGHT_ELEMENT

On entry, $\mathbf{wt}[\langle value \rangle] = \langle value \rangle$.

Constraint: when referenced, all elements of \mathbf{wt} must be non-negative.

NE_VAR_INCL_INDICATED

The number of variables, \mathbf{nvar} in the analysis $= \langle value \rangle$, while number of variables included in the analysis via array $\mathbf{isx} = \langle value \rangle$. Constraint: these two numbers must be the same.

NE_VAR_RANK

The variables are not of full rank.

7 Accuracy

The accuracy is dependent on the accuracy of the computation of the QR decomposition.

8 Parallelism and Performance

`nag_mv_discrim` (g03dac) is not threaded in any implementation.

9 Further Comments

The time will be approximately proportional to np^2 .

10 Example

The data, taken from Aitchison and Dunsmore (1975), is concerned with the diagnosis of three ‘types’ of Cushing's syndrome. The variables are the logarithms of the urinary excretion rates (mg/24hr) of two steroid metabolites. Observations for a total of 21 patients are input and the statistics computed by `nag_mv_discrim` (g03dac). The printed results show that there is evidence that the within-group variance-covariance matrices are not equal.

10.1 Program Text

```
/* nag_mv_discrim (g03dac) Example Program.
*
* NAGPRODCODE Version.
*
* Copyright 2016 Numerical Algorithms Group.
*
* Mark 26, 2016.
*/
#include <nag.h>
#include <stdio.h>
#include <nag_stlib.h>
#include <nagg03.h>

#define GMEAN(I, J) gmean[(I) *tdgmean + J]
#define X(I, J)      x[(I) *tdx + J]
int main(void)
{
    Integer exit_status = 0, i, *ing = 0, *isx = 0, j, m, n, ng, *nig = 0, nvar,
            tdgmean;
    Integer tdx;
    NagError fail;
    char weight[2];
    double *det = 0, df, *gc = 0, *gmean = 0, sig, stat, *wt = 0, *wtptr = 0;
    double *x = 0;

    INIT_FAIL(fail);

    printf("nag_mv_discrim (g03dac) Example Program Results\n\n");

    /* Skip headings in data file */
#ifdef _WIN32
    scanf_s("%*[^\n]");
#else
    scanf("%*[^\n]");
#endif

#ifdef _WIN32
    scanf_s("%" NAG_IFMT "", &n);
#else
    scanf("%" NAG_IFMT "", &n);
#endif
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "", &m);
#else
    scanf("%" NAG_IFMT "", &m);
#endif
#ifdef _WIN32
```

```

    scanf_s("%" NAG_IFMT "", &nvar);
#else
    scanf("%" NAG_IFMT "", &nvar);
#endif
#ifdef _WIN32
    scanf_s("%" NAG_IFMT "", &ng);
#else
    scanf("%" NAG_IFMT "", &ng);
#endif
#ifdef _WIN32
    scanf_s("%ls", weight, (unsigned)_countof(weight));
#else
    scanf("%ls", weight);
#endif
#endif
if (n >= 1 && nvar >= 1 && m >= nvar && ng >= 2) {
    if (!(det = NAG_ALLOC(ng, double)) ||
        !(gc = NAG_ALLOC((ng + 1) * nvar * (nvar + 1) / 2, double)) ||
        !(gmean = NAG_ALLOC(ng * nvar, double)) ||
        !(wt = NAG_ALLOC(n, double)) ||
        !(x = NAG_ALLOC(n * m, double)) ||
        !(ing = NAG_ALLOC(n, Integer)) ||
        !(isx = NAG_ALLOC(m, Integer)) || !(nig = NAG_ALLOC(ng, Integer)))
    {
        printf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }
    tdgmean = nvar;
    tdx = m;
}
else {
    printf("Invalid n or nvar or m or ng.\n");
    exit_status = 1;
    return exit_status;
}
if (*weight == 'W') {
    for (i = 0; i < n; ++i) {
        for (j = 0; j < m; ++j)
#ifdef _WIN32
            scanf_s("%lf", &x(i, j));
#else
            scanf("%lf", &x(i, j));
#endif
#ifdef _WIN32
            scanf_s("%" NAG_IFMT "", &ing[i]);
#else
            scanf("%" NAG_IFMT "", &ing[i]);
#endif
#ifdef _WIN32
            scanf_s("%lf", &wt[i]);
#else
            scanf("%lf", &wt[i]);
#endif
    }
    wtptr = wt;
}
else {
    for (i = 0; i < n; ++i) {
        for (j = 0; j < m; ++j)
#ifdef _WIN32
            scanf_s("%lf", &x(i, j));
#else
            scanf("%lf", &x(i, j));
#endif
#ifdef _WIN32
            scanf_s("%" NAG_IFMT "", &ing[i]);
#else
            scanf("%" NAG_IFMT "", &ing[i]);
#endif
    }
}
}

```

```

    for (j = 0; j < m; ++j)
#ifndef _WIN32
    scanf_s("%" NAG_IFMT "", &isx[j]);
#else
    scanf("%" NAG_IFMT "", &isx[j]);
#endif

/* nag_mv_discrim (g03dac).
 * Test for equality of within-group covariance matrices
 */
nag_mv_discrim(n, m, x, tdx, isx, nvar, ing, ng, wptr, nig,
                gmean, tdgmean, det, gc, &stat, &df, &sig, &fail);
if (fail.code != NE_NOERROR) {
    printf("Error from nag_mv_discrim (g03dac).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

printf("\nGroup means\n\n");
for (i = 0; i < ng; ++i) {
    for (j = 0; j < nvar; ++j)
        printf("%10.4f", GMEAN(i, j));
    printf("\n");
}
printf("\nLOG of determinants\n\n");
for (j = 0; j < ng; ++j)
    printf("%10.4f", det[j]);
printf("\n\n%s%7.4f\n", "stat = ", stat);
printf("%s%7.4f\n", " df = ", df);
printf("%s%7.4f\n", " sig = ", sig);
END:
NAG_FREE(det);
NAG_FREE(gc);
NAG_FREE(gmean);
NAG_FREE(wt);
NAG_FREE(x);
NAG_FREE(ing);
NAG_FREE(isx);
NAG_FREE(nig);
return exit_status;
}

```

10.2 Program Data

```

nag_mv_discrim (g03dac) Example Program Data
21 2 2 3 U
 1.1314    2.4596    1
 1.0986    0.2624    1
 0.6419   -2.3026    1
 1.3350   -3.2189    1
 1.4110    0.0953    1
 0.6419   -0.9163    1
 2.1163    0.0000    2
 1.3350   -1.6094    2
 1.3610   -0.5108    2
 2.0541    0.1823    2
 2.2083   -0.5108    2
 2.7344    1.2809    2
 2.0412    0.4700    2
 1.8718   -0.9163    2
 1.7405   -0.9163    2
 2.6101    0.4700    2
 2.3224    1.8563    3
 2.2192    2.0669    3
 2.2618    1.1314    3
 3.9853    0.9163    3
 2.7600    2.0281    3
 1         1

```

10.3 Program Results

nag_mv_discrim (g03dac) Example Program Results

Group means

1.0433	-0.6034
2.0073	-0.2060
2.7097	1.5998

LOG of determinants

-0.8273	-3.0460	-2.2877
---------	---------	---------

stat = 19.2410
df = 6.0000
sig = 0.0038
